CDX-737

10 Disc CD Changer

- 8x Oversampling, 1-Bit D/A
- Advanced ESP with 4-Mbit Buffer
- Active Servo Control
- Fast Change 10 CD Mechanism
- XA-250 10-Disc Magazine
- 110 CD Custom File Memory
- CD TEXT Capable, Memo List, Program Play
- Xplōd Cosmetics
- Super Suspension Shock Isolation
- Works with Sony UniLink Receiver/Controller

General

Output Terminals	UniLink BUS Control Output (8 Pin) Analog Audio Output (RCA)
Current Drain	800 mA (CD playback); 800 mA (during loading or ejecting a disc)
Operating Temperature	-10° C to 55° C (14° F-131° F)
Dimensions (w/h/d)	Approx. 262 x 90 x 181.5 mm (10 3/8 x 3 5/8 x 7 1/2 in.) (not including projecting parts and controls)
Weight	Approx. 2.1 kg (4 lb. 10 oz.)
Supplied Accessories	Disc Magazine (XA-250) (1) Parts for Installation and Connections (1 set)

CD Player Section

System	Compact Disc Digital Audio System
Frequency Response	10-20,000 Hz
Signal-to-Noise Ratio	94 dB
Wow and Flutter	Below measurable limit
Laser Diode Properties:	GaAlAs
Material	780 nm
Wavelength	Continuous
Emiss. Duration	Less than 44.6 uW
Laser Out Power	Measured at a distance of 200 mm from objective lens surface on Optical Pickup

Connector Panel Configuration

Design and specifications subject to change without notice.

CDX-737

10 Disc CD Changer